

F-030

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 11-214256

(43)Date of publication of application : 06.08.1999

(51)Int.Cl.

H01G 4/38

H01G 4/35

(21)Application number : 10-032234

(71)Applicant : MURATA MFG CO LTD

(22)Date of filing : 28.01.1998


(72)Inventor : NAKADA YASUHIRO
AZUMA TAKAHIRO

(54) MULTILAYER THREE-TERMINAL CAPACITOR ARRAY

(57)Abstract:

PROBLEM TO BE SOLVED: To provide a multilayer three-terminal capacitor array having a small size and a small stroke.

SOLUTION: A multilayer three-terminal capacitor array includes a multilayer body 12. The multilayer body 12 is formed by stacking a plurality of dielectric layers 14, 18, 22, 26, 30, 34, 38, and 42. Signal electrodes 16, 24, 32, and 40 are formed on the dielectric layers 14, 22, 30, and 38, respectively, with one signal electrode on each dielectric layer. Ground electrodes 20, 28, and 36 are formed on the dielectric layers 18, 26, and 34, respectively, arranged between the signal electrodes 16, 24, 32, and 40. On the outer side of the multilayer body, an outer electrode connected to both ends of each of the signal electrodes 16, 24, 32, and 40, and an outer electrode connected to the ground electrodes 20, 28, and 36 are formed. The number of ground electrodes between the signal electrodes can be two or more.



LEGAL STATUS

[Date of request for examination] 12.03.1998

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number] 2976960

[Date of registration] 10.09.1999

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2000 Japanese Patent Office